


Customer approval:



Specification:

- 1). Driving: Duty:1/64, Bias:1/9, VOUT:-4.9V,VO:-4.2V, VDD:5.0V
- 2). Viewing angle: 6 O'clock
- 3). Display mode:STN/Positive/Transflective/YG
- 4). Operating temp.: -10°C~+60°C
- 5). Storage temp.: -20°C~+70°C
- 6). Backlight: EDGE,WHITE(BLA-BLK=5.0V)
- 7). Dimensions with mark "*" are important, with mark "(") are referenced
- 8). All the raw materials are ROHS compliant

PIN	1	2	3	4	5	6	7	8	9	10
CONNECTION	VSS	VDD	V0	C/D	R/W	E	DB0	DB1	DB2	DB3
PIN	11	12	13	14	15	16	17	18	19	20
CONNECTION	DB4	DB5	DB6	DB7	CS1	CS2	/RST	VOUT	BLA	BLK

DOT SIZE
SCALE 10:1

REV	REVISION RECORD	DATE
A0	First Issue	11/12



深圳市三元鼎科技有限公司
Shenzhen TCC LCD Hi-Tech Co., Ltd.

MODEL NO. SYB12864CSV20-5C9Y13N7R-B5WG
模 组 型 号

APPROVED BY
CHECKED BY
DRAWING BY

Jequill
11/12-2010
PAGE 1 OF 1
UNIT: mm
PROJECTION 三 角 法

