



**SPECIFICATION:**

- 1). Driving: Duty:1/16, Bias:1/5, Vdd:5.0V, Vlcd:4.5V
- 2). VIEWING DIRECTION: 6 O'CLOCK
- 3). Display mode: STN/Positive/Reflective/YG
- 4). Operating temp.:0°C~+50°C
- 5). Storage temp.: -10°C~+60°C
- 6). Control IC: SPLC780D1(Or Compatible)
- 7). BACKLIGHT: NO
- 8). DIMENSIONS WITH MARK "\*" ARE IMPORTANT WITH MARK "()" ARE REFERENCED
- 9). All the raw materials are RoHS compliant

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS	VDD	V <sub>O</sub>	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	BLA	BLK

REVISION RECORD		REV	DRAWING NO.		DRAWING BY		GENERAL TOL:	
First issue		A0	SYB1604BV10				±0.2	
			DRAWING NO.		DRAWING BY		PAGE	
			APPROVED BY		CHECKED BY		1/1	
			UNTI:		mm			


**深圳市三元晶科技有限公司**  
 ShenZhen TCC LCD Hi-Tech Co., Ltd