



1	3	5	7	9	11	13	15	17	19	21
GND	V0	R/V	RES	DB1	DB3	DB5	DB7	CS2	CS4	BLA
2	4	6	8	10	12	14	16	18	20	22
VDD	RS	E	DB0	DB2	DB4	DB6	CS1	CS3	V/DUT	BLK

- SPECIFICATION:**
- 1). Driving: DUTY:1/64, BIAS:1/9, V0:-7.2V, VDD:5.0V
 - 2). Viewing angle: 6 0'CLOCK
 - 3). Display mode: STN(YELLOW-GREEN), POSITIVE, TRANSPARENT
 - 4). Operating temp: -20'C~+70'C
 - 5). Storage temp: -30'C~+80'C
 - 6). Controller IC: KS0108 (or compatible)
 - 7). Backlight: Edge White, V_{LED}=5.0V, I_{LED}=25mA
 - 8). Dimensions with mark "()" are important, with mark "*" are referenced
 - 9). All the raw materials are RoHS compliant

REV	REVISION RECORD	DATE
A		
B		
C		
D		



深圳市三元晶科技有限公司
ShenZhen TCC LCD Hi-Tech Co., Ltd.

MODEL NO. SYB24064C V11

GENERAL TOL: ±0.3

APPROVED BY

PAGE: 1 OF 1

CHECKED BY

UNIT: mm

DRAWING BY

PROJECTION

2012/04/02

三 角 法

